

2. DATOS DE INSTALACIÓN

2.1 BN-N/BN-B

Bridas de nylon blancas y negras



Características



PAHs RoHS

Poliamida 6.6

Marcado CE y Certificado UL

Datos de Instalación

CODIGO		A: Ancho [mm]	B: Largo [mm]	Rango de diámetros (mm)	Resistencia a la tracción ≥ [N]
BRIDA BLANCA	BRIDA NEGRA				
BB25080	BN25080	2,5	80	3 ÷ 14	79
BB25100	BN25100		100	3 ÷ 20,5	
BB25140	BN25140		140	3 ÷ 33	
BB25160	BN25160		160	3 ÷ 39,8	
BB25200	BN25200		200	3 ÷ 52,5	
BB36140	BN36140	3,6	140	3,5 ÷ 33	178
BB36200	BN36200		200	3,5 ÷ 46	
BB36250*	BN36250*		250	3,5 ÷ 65	
BB36300	BN36300		300	3,5 ÷ 84	
BB36370	BN36370		370	3,5 ÷ 106	
BB48120	BN48120	4,8	120	3,5 ÷ 23,8	218
BB48160	BN48160		160	3,5 ÷ 36,6	
BB48180	BN48180		180	3,5 ÷ 43	
BB48200	BN48200		200	3,5 ÷ 49,5	
BB48250	BN48250		250	3,5 ÷ 65	
BB48290	BN48290		290	3,5 ÷ 78	
BB48370	BN48370		370	3,5 ÷ 100	
BB48430	BN48430		430	3,5 ÷ 122,5	
BB76150	BN76150		7,6	150	
BB76200	BN76200	200		8,5 ÷ 50,9	
BB76290	BN76290	290		8,5 ÷ 79	
BB76370	BN76370	370		8,5 ÷ 103,5	
BB76450	BN76450	450		8,5 ÷ 130,5	
BB76540	BN76540	540		8,5 ÷ 141,59	
BB88770	BN88770	8,8	770	8,5 ÷ 230	779
BB88920	BN88920		920	8,5 ÷ 280	
BB88122	BN88122		1220	78 ÷ 375,5	
BB12225	BN12225	12,5	225	8,5 ÷ 57	1200
BB12500	BN12500		500	8,5 ÷ 156	
BB12720	BN12720		720	8,5 ÷ 216	
BB12850	BN12850		850	8,5 ÷ 263	
BB12100	BN12100		1000	8,5 ÷ 315	

PLANO

